

OPERATING INSTRUCTIONS

STARTING

- TO START, MOVE LEVER ON THROTTLE CONTROL AS FAR FORWARD AS POSSIBLE TO CHOKE POSITION.
- HOLD THE HANDLE WITH YOUR LEFT HAND AND PULL THE REWIND STARTER GRIP WITH YOUR RIGHT HAND.
- ONCE ENGINE STARTS SET THE THROTTLE LEVER TO DESIRED SPEED

STOPPING

- PULL THROTTLE LEVER TOWARD YOU TO STOP POSITION

OPERATING

- EYE PROTECTION MUST BE WORN AT ALL TIMES
- USE COMMON SENSE AND EXERCISE CAUTION AT ALL TIMES
- NEVER LEAVE MACHINE RUNNING UNATTENDED

SETTING BLADE DEPTH

- PLACE LEFT HAND ON UPPER HANDLE
- GRASP LEVER WITH LEFT HAND AND PULL TO RIGHT, WHICH DISENGAGES LEVER FROM RACHET SEGMENT ON HANDLE
- MOVE LEVER FORWARD OR BACKWARD ALONG RACHET SEGMENT AND INSERT KEY ON LEVER INTO NOTCH ON RACHET AT DESIRED DEPTH
- MOVING LEVER FORWARD DECREASES DEPTH OF CUT, MOVING LEVER BACKWARDS INCREASES DEPTH OF CUT

EDGING

- THE BLADE SHOULD BE PERPENDICULAR TO THE GROUND
- CUTTING DEPTH SHOULD BE 1" TO 1 1/2" DEEP
- ALONG SIDEWALKS AND DRIVEWAYS RUN MACHINE ON THE SOLID GROUND NOT THE GRASS